

# Adhered System Information



## Insulation Boards for use with Sarnafil Adhered Systems

Sarnafil contractors must read this information note in conjunction with Sarnafil Ltd. Application Manual 2005: Guidance Notes on the use of Insulation.

### Polyisocyanurate (Rigid Urethane)

Brand Name	Membrane		Approvals		Tapered Variant	CFC Free	HCFC Free	Source					
	G	TG76	FM	LPCB				Clyde	CPI	Keyline	Sheffield	Woods	Encon
SarnaTherm G-FM/LPC	✓	✓	✓	✓	✓	✓	✓	01324 620 318	0191 295 4000	0845 602 1111	Any Branch	01568 708 888	Any branch
Kingspan Thermaroof TR27FM/LPC	✓	✓	✓	✓	✓	✓	✓	Kingspan Insulation Ltd 01544 388601					
Kingspan Thermaroof TT47FM/LPC	✓	✓		✓	✓	✓	✓	Kingspan Insulation Ltd 01544 388601					

### Please Note

- Composite insulation's containing fibreboard must not be used, only Sarnafil recommended combinations of insulants are to be used.
- All insulation boards delivered to site must be of merchantable quality so as to permit its incorporation into the roof in an undamaged condition.
- Insulation boards should be stored under cover and on a dry platform, the insulation shrink wrapping is not adequate for weather protection.
- All roofing works must be carried out in strict accordance with the appropriate Sarnafil Ltd., BRUFMA, British Standard or British Standard Code of Practice recommendations.
- Insulation product testing is continuously being carried out by Sarnafil Ltd, for the most up to date list of products and their installation techniques, contact the Sarnafil Ltd. Technical Services Department.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and warranty are valid.

# Adhered System Information



## Insulation Boards for use with Sarnafil Adhered Systems

Sarnafil contractors must read this information note in conjunction with Sarnafil Ltd. Application Manual 2005: Guidance Notes on the use of Insulation.

### Phenolic Foam

Brand Name	Membrane		Approvals		Tapered Variant	CFC Free	HCFC Free	Source					
	G	TG76	FM	LPCB				Clyde	CPI	Keyline	Sheffield	Woods	Encon
SarnaTherm GK	✓	✓				✓		01324 620 318	0191 295 4000	0845 602 1111	Any Branch	01568 708 888	Any branch
Kooltherm K2" (Glass tissue facings)	✓	✓				✓		Kingspan Insulation Ltd 01544 388601					

### Please Note

- Composite insulation's containing fibreboard must not be used, only Sarnafil recommended combinations of insulants are to be used.
- All insulation boards delivered to site must be of merchantable quality so as to permit its incorporation into the roof in an undamaged condition.
- Insulation boards should be stored under cover and on a dry platform, the insulation shrink wrapping is not adequate for weather protection.
- All roofing works must be carried out in strict accordance with the appropriate Sarnafil Ltd., BRUFMA, British Standard or British Standard Code of Practice recommendations.
- Insulation product testing is continuously being carried out by Sarnafil Ltd, for the most up to date list of products and their installation techniques, contact the Sarnafil Ltd. Technical Services Department.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and warranty are valid.

# Adhered System Information



## Insulation Boards for use with Sarnafil Adhered Systems

Sarnafil contractors must read this information note in conjunction with Sarnafil Ltd. Application Manual 2005: Guidance Notes on the use of Insulation.

### Mineral Wool (MW)

Brand Name	Membrane		Approvals		Tapered Variant	CFC Free	HCFC Free	Source
	G	TG76	FM	LPCB				
SarnaTherm DuoRock SP-A	✓	✓	✓	✓	✓	✓	✓	Rockwool Ltd 01656 862621
Rockwool DuoRock SP-A	✓	✓	✓	✓	✓	✓	✓	Rockwool Ltd 01656 862621

### Please Note

- SarnaTherm Hardrock SP-A, Rockwool Hardrock SP-A, SarnaTherm Dual Density Hardrock SP-A and Rockwool Dual Density Hardrock SP-A are available subject to a minimum order quantity. Contact Rockwool Ltd for details.
- Composite insulation's containing fibreboard must not be used, only Sarnafil recommended combinations of insulants are to be used.
- All insulation boards delivered to site must be of merchantable quality so as to permit its incorporation into the roof in an undamaged condition.
- Insulation boards should be stored under cover and on a dry platform, the insulation shrink wrapping is not adequate for weather protection.
- All roofing works must be carried out in strict accordance with the appropriate Sarnafil Ltd., BRUFMA, British Standard or British Standard Code of Practice recommendations.
- Insulation product testing is continuously being carried out by Sarnafil Ltd, for the most up to date list of products and their installation techniques, contact the Sarnafil Ltd. Technical Services Department.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and warranty are valid.

# Adhered System Information



## Insulation Boards for use with Sarnafil Adhered Systems

Sarnafil contractors must read this information note in conjunction with Sarnafil Ltd. Application Manual 2005: Guidance Notes on the use of Insulation.

### Extruded Polystyrene

Use with Sarnacol 2142s only													
Brand Name	Membrane		Approvals		Tapered Variant	CFC Free	HCFC Free	Source					
	G	TG76	FM	LPCB				Clyde	CPI	Keyline	Sheffield	Woods	Encon
SarnaTherm XPS	✓	✓			*	✓	✓	01324 620 318	0191 295 4000	0845 602 1111	Any Branch	01568 708 888	Any branch
Extruded Polystyrene	✓	✓				✓	✓	Please contact Sarnafil Technical Services Department on 01603 748985 for guidance on the use of this insulation within a Sarnafil specification.					

\* Available on request subject to quantity

### Please Note

- Composite insulation's containing fibreboard must not be used, only Sarnafil recommended combinations of insulants are to be used.
- All insulation boards delivered to site must be of merchantable quality so as to permit its incorporation into the roof in an undamaged condition.
- Insulation boards should be stored under cover and on a dry platform, the insulation shrink wrapping is not adequate for weather protection.
- All roofing works must be carried out in strict accordance with the appropriate Sarnafil Ltd., BRUFMA, British Standard or British Standard Code of Practice recommendations.
- Insulation product testing is continuously being carried out by Sarnafil Ltd, for the most up to date list of products and their installation techniques, contact the Sarnafil Ltd. Technical Services Department.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and warranty are valid.

# Adhered System Information



## Insulation Boards for use with Sarnafil Adhered Systems

Sarnafil contractors must read this information note in conjunction with Sarnafil Ltd. Application Manual 2005: Guidance Notes on the use of Insulation.

### Expanded Polystyrene

Use with Sarnacol 2142s only								
Brand Name	Membrane		Approvals		Tapered Variant	CFC Free	HCFC Free	Source
	G	TG76	FM	LPCB				
SarnaTherm EPS I50E/200E Roofboard Unfaced	✓	✓			✓	✓	✓	Vencel Resil Ltd 0208 320 9100
Grade I50E/200E Unfaced Expanded Polystyrene	✓	✓			✓	✓	✓	Please contact Sarnafil Technical Services Department on 01603 748985 for guidance on the use of this insulation within a Sarnafil specification.

### Please Note

- Composite insulation's containing fibreboard must not be used, only Sarnafil recommended combinations of insulants are to be used.
- All insulation boards delivered to site must be of merchantable quality so as to permit its incorporation into the roof in an undamaged condition.
- Insulation boards should be stored under cover and on a dry platform, the insulation shrink wrapping is not adequate for weather protection.
- All roofing works must be carried out in strict accordance with the appropriate Sarnafil Ltd., BRUFMA, British Standard or British Standard Code of Practice recommendations.
- Insulation product testing is continuously being carried out by Sarnafil Ltd, for the most up to date list of products and their installation techniques, contact the Sarnafil Ltd. Technical Services Department.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and warranty are valid.

# Adhered System Information



## Insulation Boards for use with Sarnafil Adhered Systems

Sarnafil contractors must read this information note in conjunction with Sarnafil Ltd. Application Manual 2005: Guidance Notes on the use of Insulation.

### Cork

Brand Name	Membrane		Approvals		Tapered Variant	CFC Free	HCFC Free	Source					
	G	TG76	FM	LPCB									
Portuguese Cork only	✓	✓			✓	✓	✓	Please contact Sarnafil Technical Services Department on 01603 748985 for guidance on the use of this insulation within a Sarnafil specification.					

### Composite Insulation Board

Brand Name	Membrane		Approvals		Tapered Variant	CFC Free	HCFC Free	Source					
	G	TG76	FM	LPCB									
SarnaDeck TR31	✓	✓			✓	✓	✓	Clyde 01324 620 318	CPI 0191 295 4000	Keyline 0845 602 1111	Sheffield Any Branch	Woods 01568 708 888	Encon Any branch
Thermadeck TR31	✓	✓			✓	✓	✓	Kingspan Insulation Ltd 01544 388601					
Vapoplex	✓	✓			✓	✓	✓	Ecotherm Insulation UK Ltd 01702 520166					

\* Available on request subject to quantity

### Please Note

- Composite insulation's containing fibreboard must not be used, only Sarnafil recommended combinations of insulants are to be used.
- All insulation boards delivered to site must be of merchantable quality so as to permit its incorporation into the roof in an undamaged condition.
- Insulation boards should be stored under cover and on a dry platform, the insulation shrink wrapping is not adequate for weather protection.
- All roofing works must be carried out in strict accordance with the appropriate Sarnafil Ltd., BRUFMA, British Standard or British Standard Code of Practice recommendations.
- Insulation product testing is continuously being carried out by Sarnafil Ltd, for the most up to date list of products and their installation techniques, contact the Sarnafil Ltd. Technical Services Department.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and warranty are valid.